


(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **02288371 A**(43) Date of publication of application: **28.11.90**

(51) Int. Cl.

H01L 33/00**H01L 21/205**(21) Application number: **01110503**(22) Date of filing: **28.04.89**(71) Applicant: **TOSHIBA CORP**(72) Inventor:
IZUMITANI TOSHIHIDE
OBA YASUO
HATANO MICHIAKA**(54) SEMICONDUCTOR LIGHT EMITTING ELEMENT
AND MANUFACTURE THEREOF**

(57) Abstract:

PURPOSE: To obtain a high intensity blue light emission by alternately laminating a BP layer and a $\text{GaAl}_{1-X}\text{N}$ ($0 \leq X \leq 1$) layer, and employing a superlattice layer having a sphalerite (ZP) type crystalline structure in the $\text{GaAl}_{1-X}\text{N}$ layer.

CONSTITUTION: A n-type GaP layer 12, a n-type BP layer 13 are formed as buffer layers on a n-type GaP substrate 11, a n-type $\text{Ga}_{0.5}\text{Al}_{0.5}\text{N/BP}$ superlattice layer 14 and a p-type $\text{Ga}_{0.5}\text{Al}_{0.5}\text{N/BP}$ superlattice layer 15 are sequentially formed thereon to form a pn junction, and ohmic electrodes 16, 17 are formed on both side faces of an element. That is, the $\text{GaAl}_{1-X}\text{N}$ layer is alternately laminated with the BP layer to be easily pn-controlled with small ion properties in a ZB structure with substantially the same coupling length to form a superlattice layer to provide a compound semiconductor material of the ZB structure having both nitride direct transition type wide band gap characteristic and BP low ion properties with scarce defect occurring properties. A pn junction is composed of it. Thus, a high intensity blue light emission is obtained.

COPYRIGHT: (C)1990,JPO&Japio

